METRIC
MIL-W-89012
27 July 1990
SUPERSEDING
PS/2GC/030
May 1988

MILITARY SPECIFICATION

WORLD VECTOR SHORELINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

- 1.1 <u>Scope</u>. This specification defines the format, content, related product design and details necessary for the production of the World Vector Shoreline (WVS). The WVS is a digital data file containing the shorelines, international boundaries and country names of the world. These geographic features are required for many of the digital data bases being used to support geographic information systems and weapons systems. The WVS is a standard DMA product that has been designed for use in many different applications. Users of this product may convert the WVS data to system specific formats.
- 1.2 <u>Purpose</u>. The purpose of this specification is to assure uniformity of treatment among all mapping and charting elements engaged in a coordinated production and maintenance program for this product.

1.3 Security.

1.3.1 <u>Security classification</u>. The security classification of the products generated by the use of these specifications will be the lowest category practicable. When it is necessary to assign a security classification to the product, it will be accomplished in accordance with established national security procedures.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Director, Defense Mapping Agency, ATTN: PR, 8613 Lee Highway, Fairfax, VA 22031-2137 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A AREA MCGT

<u>DISTRIBUTION STATEMENT A.</u> Approved for public release; distribution unlimited.

Enclosure

1.3.2 <u>Product classification</u>. These Product Specifications and their resultant products are UNCLASSIFIED.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

- 2.1.1 <u>Specifications</u>, <u>standards</u>, <u>and handbooks</u>. This section is not applicable to this specification.
- 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.
- U.S. Department of State "Guide to International Boundaries" 800231 (545037) 6-86, or latest edition.

(Copies of this publication are available from The Office of The Geographer, Room 8742, Department of State, Washington, D.C. 20520.)

Federal Information Processing Standards (FIPS) Publications 3-1, 10-3, 25, and 50.

(Copies of this publication are available from the U.S. Army Publication Center, 2800 Eastern Ave., Baltimore, MD 21224.)

- 2.2 Non-Government publications. This section is not applicable to this specification.
- 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards) the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

- 3.1 <u>Accuracy</u>. The World Vector Shoreline is a generic data set for medium scale display of world shoreline, boundary and country names data, and requires the following accuracies:
- 3.1.1 Horizontal accuracy. The absolute horizontal accuracy requirement for WVS data is that 90% of all identifiable shoreline features be located within 500 meters (2.0mm at 1:250,000 scale) circular error of their true geographic positions with respect to the preferred datum (WGS). Absolute horizontal accuracy is the uncertainty of a position with respect to the horizontal datum required by the product specification, expressed in circular error (90% probability) terminology.
- 3.1.2 <u>Vertical accuracy</u>. There is no elevation data in the World Vector Shoreline product, therefore vertical accuracy is not applicable.

- 3.1.3 <u>Country name accuracy</u>. All country names in the World Vector Shoreline data set shall be those approved by the United States Board of Geographic Names (BGN), with the exception of those country names over 20 characters long, which shall be abbreviated as shown in Appendix C of this specification. International boundary information shall be in accordance with U.S. Department of State requirements as specified in "Guide to International Boundaries" 800231 (545037) 6-86, or latest edition.
- 3.2 <u>Datum</u>. Boundaries and Mean High Water shorelines in the World Vector Shoreline data set shall be referenced to the World Geodetic System (WGS) Datum and Ellipsoid. The vertical datum for shoreline features shall preferably be Mean High Water, but because of the small scale involved, shoreline features not adjusted to Mean High Water shall be used if no source on Mean High Water is available.

3.3 Product Format.

- 3.3.1 General. The WVS format makes use of a "chain-node" data structure to minimize redundant data storage. To eliminate overlaps or gaps between segments of adjacent features, each point of intersection is explicitly defined. These points are called nodes. Since a sequence of segments may outline more than one feature, features are cross-referenced to their segments (and vice versa) via unique alphanumeric feature and segment keys. By this means, a segment that is shared by multiple features is stored only once and is pointed to by the feature it comprises. feature may be comprised of many segments, or one segment may comprise several features, but in either case, each segment and each feature is stored only once (see Appendix A). Given this storage method, the order of vertices within a segment defines a direction, allowing the identification of the areas to the left and to the right of a segment (see Appendix D). For example, the left side of a boundary segment will be one country, and the right side of the segment will be another country. For shoreline segments, one side will be identified with a country, while the other side will be identified as water.
- 3.3.2 Physical characteristics of magnetic tape. WVS magnetic tapes shall be coded in ASCII format, with a physical record size of 48 bytes. Blocks shall consist of 200 records, for a total block size of 9600 bytes. Normally, magnetic tapes shall be recorded at a density of 6250 characters per inch (CPI) and shall conform with the Federal Information Processing Standards Publication 50 (FIPS PUB 50). Upon user request, magnetic tapes can be recorded at a density of 800 or 1600 CPI, and shall conform with Federal Information Processing Standards Publications 3-1 (FIPS PUB 3-1) for 800 CPI, or Publication 25 (FIPS PUB 25) for 1600 CPI.
- 3.3.3 Type of input/output. The individual records shall contain no system dependent generated control words.

- 3.3.4 File description. For production and distribution purposes, the World Vector Shoreline is divided into ten ocean basin area files (see Figure 1). Together, the ten files form a seamless world, with the exception of Central America, where there is an area of overlap between the Western North Atlantic File and the Eastern North Pacific File. The Ocean Basin Area Files described below only apply to the WVS product. The names and limits of these areas do not correspond to International Hydrographic Organization (IHO) Special Publication No. 23, Limits of Oceans and Seas. WVS files are defined as follows:
 - a. 0 Southern Ocean The area south of 60°S.
 - b. 1 Eastern North Atlantic The area bounded by a line joining:

```
80°N, 030°W;
80°N, 100°E;
35°N, 100°E;
35°N, 042°E;
25°N, 042°E;
25°N, 030°W;
80°N, 030°W.
           2 - Indian Ocean - The area bounded by a line joining:
25°N, 020°E;
25°N, 042°E;
35°N, 042°E;
35°N, 100°E;
 0°, 100°E;
 o°,
      130°E;
60°S, 130°E;
60°S, 020°E;
25°N, 020°E.
        d. 3 - Western North Pacific - The area bounded by a line joining:
80°N, 100°E;
80°N, 170°W;
 0°, 170°W;
 0°,
     100°E;
80°N, 100°E.
```

e. 4 - Eastern North Pacific - The area bounded by a line joining:

```
80°N, 170°W;
80°N, 140°W;
65°N, 140°W;
65°N, 110°W;
40°N, 110°W;
0°, 060°W;
0°, 170°W;
80°N, 170°W.
```

```
f. 5 - South Pacific - The area bounded by a line joining:
     130°E;
 ٥°,
0°, 070°W;
60°S, 070°W;
60°S, 130°E;
 0°, 130°E.
        g. 6 - Western North Atlantic - The area bounded by a line joining:
50°N, 110°W;
50°N, 075°W;
80°N, 075°W;
80°N, 030°W;
 0°, 030°W;
0°, 080°W;
25°N, 110°W;
50°N, 110°W.
         h. 7 - Eastern South Atlantic - The area bounded by a line joining:
25°N, 030°W;
25°N, 020°E;
60°S, 020°E;
60°S, 030°W;
25°N, 030°W.
         i. 8 - Western South Atlantic - The area bounded by a line joining:
 0°,
      070°W;
 0°,
      030°W;
60°S, 030°W;
60°S, 070°W;
 0°, 070°W.
         j. 9 - Arctic - The area north of a line connecting:
80°N, 140°W;
65°N, 140°W;
65°N, 110°W;
50°N, 110°W;
50°N, 075°W;
80°N, 075°W; thence eastward to
80°N, 140°W.
```




FIGURE 1. WVS File Boundaries.

3.3.5 <u>File organization</u>. The overall file organization is depicted below. Each record is 48 bytes long. A file header (4 records or 192 bytes long) starts each WVS file. Explanatory text records, if needed, follow the file header (the number of text records is given by the file header's NTEXT field). The rest of the file consists of data cells, each of which contains all features and segments for a given one degree square area on the earth surface.

FILE HEADER1 FILE HEADER2 FILE HEADER3 FILE HEADER4

TEXT RECORD1

TEXT RECORDn

CELL #1: HEADER record
FEATURE records
SEGMENT records

CELL #2: HEADER record FEATURE records SEGMENT records

CELL #3: HEADER record FEATURE records SEGMENT records

CELL #n: HEADER record
FEATURE records
SEGMENT records

3.3.6 Cell description. Each WVS file is divided into one degree by one degree cells, thus the world is divided into 64,800 cells. WVS data are collected into cells to facilitate windowing, repartitioning, and future expansions of the data set. Each cell is numbered in accordance with the latitude and longitude of its southwest corner. Cells are numbered starting at 90 degrees South latitude/180 degrees longitude and extend eastward from Cell # 1 to Cell # 360. The next row of cells starts at 89 degrees South latitude and extends eastward from Cell # 361 to Cell # 720. This sequence continues northward until the last row of cells, at 89. North latitude are numbered (cell #64441 to cell #64800). See Figure 2.

-						
	# 64800	# 64441	# 64442	# 64443	# 64444	
			•			
	# 720	# 361	# 362	# 363	# 364	
	# 360	# 1	# 2	# 3	# 4	
•	179°E	180°	179°W	178°W	177°W	176°W

FIGURE 2. Example of WVS Cell Numbering.

- 3.3.7 <u>Feature description</u>. The WVS consists of shorelines, international boundaries/lines of separation, and names data.
- a. The shoreline data are produced from cartographic or imagery source material and should not be displayed or plotted at a scale larger than 1:250,000.
- b. International boundary data are primarily extracted from small scale cartographic sources and do not show the same level of detail that is shown for shoreline data.
- (1) Each side of an international boundary is tagged with an appropriate country code. Country codes are associated with either the left side or the right side of the boundary line as defined by the direction of digitization. In a similar manner, the land side of the shoreline is tagged with the country code and the water side is tagged with a special two-digit code as follows: The first digit is the file number (see 3.3.4). The second digit is a code for the continental or island landmass associated with the shoreline (for WVS database Edition One only). All landmasses that are not the mainlands of the seven continents are considered islands.

The continent codes are:

Asia -A
Africa - F
North America - N
South America - S
Antarctic Continent - T
Australian Continent - U
Europe - E
Island - I

- (2) Country codes are based on the two letter Federal Information Processing Standard coding scheme contained in FIPS Pub 10-3. See Appendix C.
- c. Country names, as opposed to country codes, shall be the "short form" approved by the United States Board on Geographic Names (BGN), with the exception that those country names that exceed twenty characters in length shall be compressed as listed in Appendix C. The ability to display or plot a country name within the boundary lines of that country is dependent upon the display scale and hardware characteristics of the individual application. The approximate center of the polygon formed by a country's boundary lines (and shoreline, if any) within a WVS file is included as a potential location for the display of the country name. The approximate center values apply only to that part of the country located within a WVS file's coverage. This set of feature records will be part of the data cell which includes the approximate center values. The approximate center is determined through visual estimation and is not mathematically calculated.
- 3.3.8 <u>Feature coordinates</u>. All coordinates are decimal values ordered first by the longitude component, and then by the latitude component, to align with the Cartesian system's standard (X,Y) ordering. (Note This ordering method is opposite to the more traditional method of cartographic positioning, which uses latitude-longitude ordering.)
- a. Header record coordinates (in both File and Cell Headers) have an implied decimal point at 0.0001 (or the reciprocal of ORIGDEC, given in File Header #1). An implied "+" indicates east or north and an encoded "-" indicates west or south, following the International Standard (#6709-1983). 180 degrees longitude is always listed as -180 in the WVS data set. Thus, a header record coordinate (0365000,-750000) refers to 36.5 degrees East, 75 degrees South.
- b. In data records, however, coordinates (XSECONDS, YSECONDS) are given in positive 0.1 seconds (or /DATADEC, given in File Header #1) of offset from the cell origin. The cell origin (LNGCELL, LATCELL) is the southwest corner of a cell. For example, given the YSECONDS data value 003480 in a LATCELL of -750000 with a DATADEC value of 10, the full latitude is computed as follows:

latitude degrees = (LATCELL / ORIGDEC) deg +
[(YSECONDS / DATADEC) sec / 3600 sec/deg]

- = (-750000 / 10000) deg + [(3480 / 10) / 3600)] deg
- = -75.0000 deg + 0.09667 deg
- = -74.90333 degrees, or
- 74 deg 54 min 12.0 sec South

3.3.9 File structure.

- a. File header records. See Appendix B for a sample WVS file listing.
 - (1) File Header #1: Title, source and coordinate conversions.

Name	Format	Description
TITLE	A20	Title of the file (Names are recorded without spaces)
FILENUM	I	File number (refer to Figure 1)
EDITION	I2,1X	Edition number
PRODUCER	A8,1X	USDMAHTC
COMPDATE	14,1X	compilation date (YYMM) of this data set
ORIGDEC	15	inverse of implied decimal for LNG, LAT origin points given in file and cell headers. If ORIGDEC = 10,000, divide LNG and LAT origins by 10,000.
DATADEC	15	Inverse of implied decimal for LNG, LAT data points in segment records. If DATADEC= 10, divide LNG and LAT data points by 10.

(2) File Header #2: Geographic boundaries of file.

Note - This file header is included for the use of future digital products which may use the WVS format.

Name	Format	Description
LNGOR	18	Longitude of global file origin, from which all cell numbering begins (global origin = -180).*
LATOR	17	Latitude of global file origin, from which cell numbering begins (global origin = -90).*
XMAP	13	Width of file in degrees longitude (full world = 360).*
LNGSW	18	Longitude of southwest file corner.*
LATSW	17	Latitude of southwest file corner.*
LNGNE	18	Longitude of northeast file corner.*
LATNE	17	Latitude of northeast file corner.*

For WVS Edition One:

LNGOR = -1800000

LATOR = -900000

XMAP = 360

LNGSW = -1800000

LATSW = -900000

LNGNE = -1800000

LATNE = -600000

- * Coordinates measured in degrees from origin; divide by ORIGDEC.
 - (3) File Header #3: Feature counts.

Name	Format	Description
NFEA	17,1X	Total number. of features in file.
NPOINTS	17,1X	Number of point features.
NLINES	17,1X	Number of line features.
NAREAS	17,1X	Number of area features.
NCODES	14,1X	Number of different FACS codes in
		file (e.g. feature types).
MSEGperFEA	13,1X	Maximum number of segments comprising a feature.
MFEAperSEG	12	Maximum number of features depicted by a segment.
BLANK	5X	- ·

(4) File Header #4: Segment, cell and text record counts.

Name	Format	Description
NSEG MVRTperSEG	I7,1X I5,1X	Total number of segments in file. Maximum number of vertices in a
ISCALE	19,1X	segment. Scale reciprocal (e.g. 250000 =
XCELL	I4,1X	1:250,000). Width (X) of cells in degrees of LNG.
VODIT	74 111	(Implied decimal = 0.1). 0010 for WVS Edition One.
YCELL	I4,1X	Height (Y) of cells in degrees of LAT.(Implied decimal = 0.1). 0010 for WVS Edition One.
NCELLS	I6,1X	Number of cells in the file.
Name	Format	Description
NTEXT	14	Number of text records to follow.
BLANK	3X	

(5) Text Records: Format = A48. The number of text records is NTEXT.

- b. Data cell records. Each of the cells contained in the file is represented by a header. If a cell is not empty (NSEGinCELL > 0), the header is followed by the cell's feature records, which are followed by a series of segment records. The formats of the cell header, feature records, and segment records follow.
- (1) Cell header record. Each data cell starts with a one-record header containing a cell identification number, the cell origin (longitude and latitude of the lower left corner of the cell), the number of features and segments in the cell, and the number of 48-byte feature and segment records the cell contains. Headers for empty cells are included for algorithmic simplicity and future data enhancements. The feature and segment record counts provided in the header can be used to skip directly to the cell's segment data for simple graphic applications, or to skip over one cell to the next cell.

Name	Format	Description
CELLFLAG CELLTYPE	Al Al	New cell marker = "C". Key to cell contents: "L" = all land, "W" = all water, "C" = combination.
NCELLHEAD	Il	Number of additional cell header records that immediately follow this one (for WVS Edition One, NCELLHEAD= 0).
CELLNUM	16	Cell number (1 - 64800)
LNGCELL	18	Longitude of southwest cell corner* (range from -1800000 to 1790000).
LATCELL	17	Latitude of southwest cell corner* (range from -900000 to 890000).
NFEAinCELL	I5	Number of features in cell.
NSEGinCELL	15	Number of segments in cell.
NFEAREC	17	Number of 48-byte feature records in cell. Feature header records, extra data records, and feature data records are the possible feature records.
NSEGREC	17	Number of 48-byte segment records in cell NFEAREC + NSEGREC + NCELLHEAD = number of records preceding the next cell. Segment header records, extra feature reference records, and segment data records are the possible segment records.

^{*} Cell origins measured in degrees; divide by ORIGDEC (in File Header #1).

⁽²⁾ Cell feature records. Each cell contains a certain number of features, equal to the NFEAinCELL value. Each feature has a header record, an extra attribute record, if required by the type of feature, and data records.

(a) Feature header records: Each feature has at least one feature header record to identify the feature and its associated attributes, segment records, and (feature) data records.

Name	Format	Description
FEAFLAG FEANUM	A3 17	New feature marker = "FEA" (constant). Unique feature identification number (unique in current cell) used to key from segment records.
FEATYPE	Al	"P" is point, "L" is line, and "A" is area feature (WVS Edition One has only point features for names and only line features for shorelines and boundaries).
FACS	A5	Code indicating FACS feature type (see 3.4).
ATTRIB	A24	Attribute buffer; format based on feature type. The following format is used for Shorelines and Boundaries: ATTVAL 3A6 Up to three attributes, each with a three letter attribute code and three digit value code. CONT1 I1 Edge code where feature enters cell from adjacent cell. For features that commence within the cell, CONT1 = 0. (see Figure 3)
		CONT2 Il Edge code where feature exits cell to adjacent cell. For features that terminate within the cell, CONT2 = 0. (see Figure 3)
		FEALAB A4 Country code (see Appendix C), or file/continent code (see 3.3.7) to left and right of feature, respectively.
		The following format is used for
		Country Names:
		CCODE A2 2 letter country code.
		CNAME A20 Country name.
		SCODE A2 Sovereignty code (2

letter country code).

Name	Format	Description
NSEGINFEA	13	Number of segments comprising this feature.
NATTR	13	Number of extra attribute records that immediately follow this header record. For shorelines and boundaries, NATTR = 0; for country names, NATTR = 1.
NFDATAREC	12	Number of feature data records that follow.

3	4	5
2	cell of interest	6
1	8	7

FIGURE 3. Edge Codes.

(b) Extra attribute records: For WVS database Edition One, only country names use extra attribute records to describe the country's extent and the position of the country's name (approximate center). A country name shall be associated with the polygon formed by the appropriate boundary lines and shorelines. The maximum extent and approximate center of each polygon shall be determined through visual estimation. The following is a description of the country name extra attribute format.

Name	Format	Description
MINLNG	18	Minimum longitude* (first integer meridian west of the country).
MINLAT	17	Minimum latitude* (first integer parallel south of the country).
MAXLNG	18	Maximum longitude* (first integer meridian east of the country).
MAXLAT	17	Maximum latitude* (first integer parallel north of the country).
CENTLNG	18	Approximate center longitude.*
CENTLAT	17	Approximate center latitude.*
BLANK	3X	

- * Coordinates measured in degrees; divide by ORIGDEC (in File Header #1).
- (c) Feature data records: All component segments of the current feature are listed here. Segments are identified by unique numeric keys (SEGNUM), and the ordering of points is provided (SEGDIR). Up to six pairs of (SEGNUM, SEGDIR) can be stored in a feature data record. As described in feature header record, the total number of pairs = NSEGinFEA; total number of feature data records = NFDATAREC.

Name	Format	Description
SEGNUM	17	Segment identification number (unique in current cell) used to key to a segment record in this segment.
Name SEGDIR	Format Al	Description Direction of points in segment: "F" = Forward, or same order as stored "R" = Reverse of stored order "D" = Disjointed, same order as stored "E" = Disjointed, reverse order "I" = Inside, same order as stored "J" = Inside, reverse order

See Appendix D for explanation of terms.

- (3) Segment records. Each cell contains the number of segments given in NSEGinCELL. Each segment has a header record, extra feature reference records if required, and (segment) data records.
- (a) Segment header records: All features delineated by the segment are referenced here. Features are referenced by unique numeric keys (FEANUM) and feature orientation (FEAORI). Up to three pairs of (FEANUM, FEAORI) fit in a single segment header record. If NFEAinSEG > 3, the overflow feature references are stored in additional 48-byte extra feature reference records.

Name	Format	Description
SEGFLAG	A3	New segment marker = "SEG"
SEGNUM	17	Segment key: a unique segment identification number.
NVERTS	15	Number of vertices (x,y data points) in segment.
NFEAinSEG	12	Number of features to which this segment belongs.
NXFEARECS	12	Number of extra feature reference records immediately following this header record.
NSDATAREC	15	Number of segment data records that follow.
FEANUM	17	Feature key: a number identifying a

Name	Format	Description	
		feature to which this segment belongs.	
FEAORI	Al	Feature orientation: the feature being represented: "L" = feature is left of line segment "R" = feature is right of line segment "C" = feature is coincident with line segment (Point features are defined to be coincident with segments)	
FEANUM	17	•	
FEAORI	Al		
FEANUM	17		
FEAORI	Al		

(b) Extra feature reference records: The number of extra feature reference records used is NXFEARECS. The format is a repeating sequence of up to six pairs of (FEANUM, FEAORI), continued from the segment header record.

(c) Segment data records: A listing of NVERTS segment vertices, with coordinates expressed in longitude, latitude (XSECONDS, YSECONDS) pairs, up to four pairs per data record. The total number of data records is NSDATAREC, listed in the segment header record. Coordinates are stored in seconds of offset from the current cell's origin, with an implied decimal point of DATADEC.

To transform the vertices to global coordinates:

longitude = (LNGCELL / ORIGDEC) + [(XSECONDS / DATADEC) / 3600]
latitude = (LATCELL / ORIGDEC) + [(YSECONDS / DATADEC) / 3600]

Name	Format	Description
XSECONDS	16	Longitude in seconds of offset from cell origin.
YSECONDS	16	Latitude in seconds of offset from cell origin.

3.4 Feature/Attribute Requirements.

3.4.1 <u>General</u>. This section identifies the features required in the World Vector Shoreline (WVS) file and provides additional information about each feature, and details about how and when it is used.

The features and attributes described in this section are based on the DMA Feature/Attribute Coding Standard (FACS), October 1987 Edition, contained in Section 100 (Glossary) of the MARK 90 Standards Document. The FACS provides a standard list of features, attributes, and attribute values used in the collection of digital data within DMA.

3.4.2 FACS features. Each feature is assigned a five digit alphanumeric FACS code. FACS attributes are used to further describe or categorize a feature and are assigned a three letter alphabetic code. For each attribute several attribute values are shown to describe the feature at the most detailed level. The following list provides the FACS Numbers and feature names for all of the FACS features that are considered shoreline features for the WVS product. All of these features are digitized and coded as Coastal Shoreline (2A010) if they meet the inclusion conditions given for each feature in the following pages of this section.

2A010	Coastal Sh	noreline
	for the WVS	product, the following FACS features are also
	coded as Coa	stal Shoreline (2A010).
	2B020	Breakwater
	2B140	Jetty
	2B190	Pier/Wharf
	2B230	Seawall
	2н020	Canal
	2H080	Lake/Pond
	2H140	River/Stream
	2J030	Glacier

The following boundary and name features are included in the WVS file.

6A095	Boundary
6A115	No Defined Boundary
6A125	Other Line of Separation
9A010	Name Location

The remainder of 3.4 is organized by the FACS features listed above. Information concerning attributes, inclusion conditions, and product generation rules for the WVS files is presented in the format shown in Figure 4.

FACS Feature: FACS Feature name FACS Number: 5 digit

alphanumeric code

<u>Definition</u>: FACS Feature definition

Attributes: Attribute Values:

Attribute name (3-letter code) - followed by the attribute definition. definition,

Value number and value name, followed by the value

if necessary

All required attributes and values are listed.

<u>Inclusion Condition</u>: Criteria that determine when the FACS feature is included in the World Vector Shoreline (WVS) data set.

<u>Product Generation Rules</u>: Rules that describe how a FACS feature is shown and any other rules or special treatment required by the feature.

FIGURE 4. FACS Feature Information Format.

a. FACS Feature: Coastal Shoreline FACS Number: 2A010

<u>Definition</u>: The line where a landmass is in contact with a body of open water (excluding inland hydrography) at a specified vertical datum.

Attributes:

Attribute Values:

Vertical Datum Category (VDC) - The vertical datum to which the feature is referenced.

VDC007 Mean High Water

<u>Inclusion Conditions</u>: Coastal Shorelines are included in the WVS for the seven continents listed in 3.3.7, and all islands that have a length greater than 180 meters. The length of an island is the longer of two linear axes.

Product Generation Rules:

- 1. Generalization shall be commensurate with a graphic scale of 1:250,000.
- 2. Shorelines surrounding bays, fjords, and inlets are excluded when these features have entrances with widths less than 70 meters. The bay, fjord, or inlet is closed off by shoreline at the point where it becomes less than 70 meters wide.
- If a group of islands exist in a cluster, and the islands are less than 70 meters apart, they are generalized and shown as a single island.
- 4. If an island is less than 70 meters from the shoreline of the mainland or a larger island, it is included as part of the larger feature.
- 5. Shoreline features shall be tagged with country codes. A two letter country code is added to the landward side of the shoreline feature. See Appendix C. The country code for the seaward side of the shoreline feature consists of a one digit file number (see 3.3.4), followed by one alpha character continent code (see 3.3.7). The data field FEALAB shall be filled with the two letter country code and the file/continent code. The first two characters label the left side of the feature, as defined by the direction of digitization. The second two characters label the right side of the feature.

b. FACS Feature: Breakwater FACS Number: 2B020

<u>Definition</u>: A structure which protects a harbor or beach from forces of

the sea.

Attributes: Attribute Values:

Vertical Reference Category (VRC) -Vertical Reference Category (VRC) -Not Relative location referenced to a sounding datum, unless otherwise indicated.

VRC001 Above Surface/Does

Cover (at High Water)

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length.

WID > 70 meters

Inclusion Conditions: Breakwaters are included if they extend above high water and have a width greater than 70 meters.

Product Generation Rules:

1. Breakwaters are treated as coastal shoreline (2A010). c. FACS Feature: Jetty FACS Number: 2B140

<u>Definition</u>: A man-made barrier built out into the water to restrain or direct currents or waves.

Attributes: Attribute Values:

Vertical Reference Category (VRC) -

VRC001 Above Surface/Does

Cover (at High Water)

Relative location referenced to a sounding datum, unless otherwise indicated.

WID > 70 meters

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length.

Inclusion Conditions: Jetties are included if they extend above high water and have a width greater than 70 meters.

Product Generation Rules:

1. Jetties are treated as coastal shoreline (2A010).

d. FACS Feature: Pier/Wharf FACS Number: 2B190

<u>Definition</u>: Berthing places for vessels. Pier - a long narrow structure extending into the water; Wharf - approximately parallel to the shoreline and accommodates ships on one side only.

Attributes:

Attribute Values:

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length.

WID > 70 meters

<u>Inclusion Conditions</u>: Piers are included if the width is greater than 70 meters. Wharves are included to connect segments of included shoreline (2A010).

Product Generation Rules:

1. Piers and wharves are treated as coastal shoreline (2A010).

e. FACS Feature: Seawall FACS Number: 2B230

<u>Definition</u>: A structure built to protect the shore from erosion.

Attributes: Attribute Values:

No attributes required.

Inclusion Conditions: Seawalls are required if they connect segments of included coastal shoreline (2A010).

Product Generation Rules:

1. Seawalls are treated as coastal shoreline (2A010).

f. FACS Feature: Canal FACS Number: 2H020

<u>Definition</u>: A man-made or improved natural waterway used for transportation.

Attributes: Attribute Values:

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length.

WID > 70 meters

<u>Inclusion Conditions</u>: Canals with a width of greater than 70 meters are shown for a distance of 1852 meters (1 nautical mile) inland from the well defined canal entrance.

Product Generation Rules:

1. Canals are treated as coastal shoreline (2A010).

g. FACS Feature: Lake/Pond FACS Number: 2H080

<u>Definition</u>: An inland body of water surrounded by land, where no appreciable current or flow pattern is evident.

Attributes: Attribute Values:

Distance From Shoreline (DFS) - The distance between the feature and the closest coastal shoreline (2A010).

DFS < 1852 meters

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length. WID > 70 meters

<u>Inclusion Conditions</u>: Lakes are included if they are located less than 1852 meters (1 nautical mile) from the coastal shoreline and they are connected to the sea by a river that has a width greater than 70 meters.

Product Generation Rules:

1. Lakes are treated as coastal shoreline (2A010).

h. FACS Feature: River/Stream FACS Number: 2H140

<u>Definition</u>: A natural flowing watercourse.

Attributes: Attribute Values:

Width (WID) - A measurement of the shorter of two linear axes in meters. For a square feature, measure either axis. For a round feature, width shall be equal to length.

<u>Inclusion Conditions</u>: Rivers with a width of greater than 70 meters are shown for a distance of 1852 meters (1 nautical mile) inland from the well defined river mouth.

WID > 70 meters

Product Generation Rules:

1. Rivers are treated as coastal shoreline (2A010).

i. FACS Feature: Glacier FACS Number: 2J030

<u>Definition</u>: A large mass of snow and ice moving slowly down slope or valley from above the snowline.

Attributes:

Attribute Values:

No attributes required.

<u>Inclusion Conditions</u>: Glaciers are included if the outer extremities of the glacier form the apparent shoreline.

Product Generation Rules:

 The seaward edge of the glacier is treated as coastal shoreline (2A010).

MIL-W-89012

j. FACS Feature: Boundary FACS Number: 6A095

<u>Definition</u>: A line of demarcation between political areas.

Attributes: Attribute Values:

Boundary Status (BST) - Degree of BST001 Recognized agreement on or precision of a BST002 Disputed boundary. BST003 Indefinite

First Name (NM3) - Name of political NM3 any

entity on one side of a boundary

Second Name (NM4) - Name of political NM4 any entity on other side of a boundary

Use Status (USE) - Identifies the USE023 International

primary user, function, or controlling authority.

Inclusion Conditions: All International Boundaries are included.

Product Generation Rules:

1. The first two alphanumeric characters in the FEALAB field of the WVS data set shall be the country code (See Appendix C) of the country on the left side of the feature, as defined by the direction of digitization. The second two alphanumeric characters in FEALAB shall be the country code of the country on the right side of the feature.

k. FACS Feature: No Defined Boundary FACS Number: 6A115

<u>Definition</u>: A line representing an arbitrary closure of polygons for areas whenno defined boundary exists.

any

Attributes: Attribute Values:

First Name (NM3) - Name of political

entity on one side of a boundary

Second Name (NM4) - Name of political NM4 any

entity on other side of a boundary

<u>Inclusion Conditions</u>: Lines representing no defined boundary are required to make closed polygons of the following countries:

Oman Saudi Arabia Yemen (Aden) United Arab Emirates Yemen (Sanna)

Product Generation Rules

1. The first two alphanumeric characters in the FEALAB field of the WVS data set shall be the oountry code (See Appendix C) of the country on the left side of the feature, as defined by the direction of digitization. The second two alphanumeric characters in FEALAB shall be the country code of the country on the right side of the feature.

1. FACS Feature: Other Line of FACS Number: 6A025

Separation

<u>Definition</u>: A line separating countries or areas that is not recognized as a political boundary.

Attributes Attribute Values

First Name (NM3) - Name of political NM3 any

entity on one side of a boundary

Second Name (NM4) - Name of political NM4 any entity on other side of a boundary

<u>Inclusion Conditions</u>: Other lines of separation are required for the following areas:

Administrative Boundary between Sudan/Egypt and Sudan/Kenya.

Administrative Line between Oman/Yemen (Aden) and Oman/United Arab Emirates.

Armistice Line for the borders of Israel.

Cease-Fire Line between India/Pakistan.

Claim Line between China/India, for that area claimed by India.

Demarcation Line between Democratic Peoples Republic of Korea/Republic of Korea.

Limit of Control between China/India, for that area controlled by China.

Lines of Separation around Guantanamo Bay, Berlin, and the border between German Democratic Republic/Federal Republic of Germany.

Provisional Administrative Line between Ethiopia/Somalia.

Zone of Occupation for the West Bank and Gaza Strip.

Product Generation Rules:

1. The first two alphanumeric characters in the FEALAB field of the WVS data set shall be the country code (See Appendix C) of the country on the left side of the feature, as defined by the direction of digitization. The second two alphanumeric characters in FEALAB shall be the country code of the country on the right side of the feature.

MIL-W-89012

m. FACS Feature: Name Location FACS Number: 9A010

(NOT IN FACS)

<u>Definition</u>: A geographic position located at the approximate center of a named area where a place name is displayed.

Attributes: Attribute Values:

Name Category (NAM) - The proper name, identifying code, or number of a

NAM000 any

feature.

<u>Inclusion Conditions</u>: One Name Location is required for each polygon included in the WVS file.

Product Generation Rules:

- 1. The country name shall be shown by the WVS data field CNAME (see Appendix C).
- The position of the country name shall be located approximately in the center of the country. The latitude of this position shall be recorded in the WVS data field CENTLAT. The longitude of this position shall be recorded in the WVS data field CENTLNG.
- Only those countries listed by two letter country codes in Appendix C are included in the WVS.
- 4. Generally, all polygons in the WVS file require a name location point; however, under certain conditions this would lead to an excessive number of names included in the WVS data set. Therefore, name location points of islands may be thinned, based on the following criteria:
 - a. If all islands in a group belong to the same country, it is not necessary to place a name location point in each island polygon. Instead, a name location point shall be positioned in the approximate center of the island group.
 - b. If islands in a group belong to different countries, a name location point shall be positioned in the approximate center of each island polygon.
 - c. Name location points shall be included on all islands that have an area greater than 100 square kilometers.

4. QUALITY ASSURANCE

- 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.
- 4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.
- 4.1.2 <u>Final product quality</u>. Final product quality will reflect the quality expressed by each applicable military standard.
 - 5. PACKAGING This section is not applicable to this specification.
 - 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

- 6.1 <u>Definitions</u>. This section is not applicable to this specification.
- 6.2 <u>Supersession</u>. These specifications supersede Defense Mapping Agency Product Specifications for World Vector Shoreline, PS/2GC/030, First Edition, May 1988.
- 6.3 <u>Intended use</u>. World Vector Shoreline is intended to be used in TOMAHAWK shipboard and shore mission planning, AEGIS command displays, Tactical Flag Command Center displays, and various other computer display command and control systems.
- 6.4 International Standardization Agreements. Certain provisions of this specification are subject of international standardization agreement. When amendment, revision, or cancellation of this specification is proposed that will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels, including departmental standardization offices, to change the agreement or make other appropriate accommodations.

- 6.4.1 <u>International Standardization Agreements (STANAGS)</u>. This section is not applicable to this specification.
- 6.4.2 <u>Ouadripartite Standardization Agreements (OSTAGs)</u>. This section is not applicable to this specification.
- 6.4.3 <u>Air Standardization Coordinating Committee Agreements (ASCC AIR STDs/STDs/ADV PUBs)</u>. This section is not applicable to this specification.
- 6.4.4 <u>International MC&G Agreements</u>. This section is not applicable to this specification.
- 6.4.5 <u>Executive Orders</u>. This section is not applicable to this specification.
- 6.4.6 <u>Inter-Agency Agreements</u>. This section is not applicable to this specification.
- 6.4.7 Other documentation. This section is not applicable to this specification.

APPENDIX A


COMPARISON OF "CHAIN-NODE" WITH SEQUENTIALLY STORED DATA


10. GENERAL

- 10.1 <u>Scope</u>. An important aspect of WVS is the use of a "chain-node" data structure to store cartographic features. This data structure, adapted from DMA's Standard Linear Format (SLF), eliminates both redundant segment storage and erroneous overlaps and gaps between segments of adjacent features. The following example serves to show the differences between storing data sequentially and structuring the data in a chain-node form.
- 10.2 <u>Sequential structure</u>. Figure 5a shows three adjacent areal features as they might appear on a map. In the sequential storage method, each feature would be treated as a separate polygon, digitized independently (Figure 5b), and stored as a string of X,Y coordinates. The common boundary between two abutting features would be digitized twice, and the two versions may not coincide. This often results in gaps or overlaps along the boundary (Figure 5c).
- 10.3 <u>Chain-node structure</u>. In the chain-node method, the segments that comprise the features are digitized as shown in Figure 5d. The common boundary between adjacent features is digitized and stored only once, so that the features abut precisely. The coordinates of each segment are stored with a unique alphanumeric segment ID with pointers to the features associated with that segment. Each feature is also stored with a unique ID with pointers to the segments that comprise it. Therefore, features may be displayed either separately (Figure 5e) or together (Figure 5f). Since a segment may be used more than once in displaying adjacent features, WVS provides a segment direction indicator (e.g., Forward or Reverse) to order the segment coordinates and to delineate features properly. Appendix D describes in greater detail the segment directions used by WVS.
- 20. APPLICABLE DOCUMENTS This section is not applicable to this Appendix.

SEQUENTIAL DATA STORAGE


CHAIN-NODE DATA STORAGE






(a) Features on a map


(d) Digitized Segments






(b) Digitized Polygons

(e) Individually Displayed WVS Features





(c) Display of Data Stored Sequentially

(f) Display of Data Stored in Chain-Node Structure

Sequential vs. Chain-Node Methods of Cartographic Data Storage. Arrows indicate the ordering of coordinates within a segment: solid lines represent digitized outlines; dashed lines represent true boundaries.

FIGURE 5. Sequential vs. chain-node methods of cartographic data storage.

APPENDIX B

SAMPLE WVS FILE LISTING

10.	GENERAL
-----	---------

10.1 Scope. This appendix illustrates how WVS files are organized. This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

File Header #1

ITIT2 IXIA8 | IXIT4 | IXIT5 | IT5 A20 TITLE PRODUCER COMPDATE DATADEC ORIGDEC EDITION FILENUM FileHeader #2

117 113 118 117 118 <u> 117</u> LNGOR LATOR LNGSW LATSW LNGNE LATNE XMAP

File Header #3

IXII7 IXII7 IXII7 IXII4 IXII3 IXII2IXXXXXI NFEA NPOINTS NLINES NAREAS NCODES MFEAperSEG MSEGperFEA

File Header #4

117 IXIIS IXII9 IXII4 IXII4 IXII6 IXII4 IXXXI ISCALE XCELL YCELL NCELLS NTEXT NSEG MVERTperSEG

Cell Header

IAIAIIII6 II8

LNGCELL LATCELL

NFEAREC NSEGREC

CELLNUM NSEGinCELL NFEAinCELL NCELLHEAD

CELLTYPE CELLFLAG

MIL-W-89012

Feature Header (Shorelines/Boundaries)

1A3 1A7					
FEANUM FACS ATTVAL ATTVAL ATT	VAL NFDATAREC				
FEAFLAG FEATYPE	NATTR				
	NSEGinFEA				
	FEALAB				
	CONT2				
	CONT1				
Feature Header	•				
(Country Names					
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
IA3 II7 IAIA5 IA2IA20	<u> 182 13 13 12 </u>				
FEANUM FACS CNAME	NFDATAREC				
FEAFLAG FEATYPE CCODE	NATTR				
	NSEGINFEA				
	SCODE				
Extra Attribute Re	cord				
<u> </u>	T8 IT7 IXXXI				
MINLNG MINLAT MAXLNG MAXLAT					
Feature Data Rece	ord				
II7 IAII7 IAII7 IAII7	IAII7 IAII7 IAI				
SEGNUM SEGNUM SEGNUM SEGNUM					
SEGNOM SEGNOM SEGNOM SEGNOM SEGDIR	SEGDIR SEGDIR				
obobin obobin obobin					
Segment Header Record					
	15177 15177 151				
1A3 17 15 12112 15 17	PENNIM PENNIM PENCET				
	FEANUM FEANUM FEAORI				
SEGFLAG NSDATAREC	PEAURI PEAURI				
NXFEARECS					
NFEAinSEG					

Segment Data Record

| II6 | II6

20. APPLICABLE DOCUMENTS This section is not applicable to this appendix.

APPENDIX C

COUNTRY CODES AND COUNTRY NAMES

10. GENERAL

- 10.1 <u>Scope</u>. The following pages list country codes and country names used in the attribute buffer (ATTRIB field) of the Feature Header Records (see 3.3.8.2.2). These codes and names are based on the Federal Information Processing Standards Publication Countries, Dependencies, Areas of Special Sovereignty, and Their Principle Administrative Divisions (FIPS Pub. 10-3). This appendix is a mandatory part of the specification. The information contained herein is intended for compliance.
- 10.2 <u>Abbreviations</u>. The attribute buffer contains only twenty characters for country names. The following abbreviations shall be used to enable the country names to fit into the available space. These abbreviations apply to the WVS product only.

&	and
BR	British
FED	Federated
FR	France or French
I	Island
IS	Island(s)
P	Peoples
R	Republic
S	South
SOC	Socialist
sov	Soviet
STS	States
TE	Territory
TR	Trust
U	Union
UAE	United Arab Emirates
UN	United Nations
VINC	Vincent
ZO	Neutral Zone

10.3 Country codes and names.

Country	Country		
Code	Name		
AA	ARUBA		
AF	AFGHANISTAN		
AL	ALBANIA		
AG	ALGERIA		
AQ	AMERICAN SAMOA		
AN	ANDORRA		
AO	ANGOLA		
AV	ANGUILLA		
AY	ANTARCTICA		
AC.	ANTIGUA AND BARBUDA		

	_
AR	ARGENTINA
AT	ASHMORE&CARTIER IS
AS	AUSTRALIA
AU	AUSTRIA
BF	BAHAMAS
BA	BAHRAIN
FQ	BAKER ISLAND
BG	BANGLADESH
BB	BARBADOS
BS	BASSAS DA INDIA
BE	BELGIUM
BH	BELIZE
BN	BENIN
BD	BERMUDA
BT	BHUTAN
BL	BOLIVIA
BC	BOTSWANA
BV	BOUVET ISLAND
BR	BRAZIL
10	BR INDIAN OCEAN TE
VI	BRITISH VIRGIN IS
BX	BRUNEI
BU	BULGARIA
υv	BURKINA
BM	BURMA
BY	BURUNDI
CB	CAMBODIA
CM	CAMEROON
CA	CANADA
CV	CAPE VERDE
CI	CAYMAN ISLANDS
CT	CENTRAL AFRICAN R
CD	CHAD
CI	CHILE
СН	CHINA
KT	CHRISTMAS ISLAND
IP	CLIPPERTON ISLAND
CK	COCOS (KEELING) IS
CO	COLOMBIA
CN	COMOROS
CF	CONGO
CM	COOK ISLANDS
CR	CORAL SEA ISLANDS
CS	COSTA RICA
CU	CUBA
CY	CYPRUS
CZ	CZECHOSLOVAKIA
DA	DENMARK
DJ	DJIBOUTI
DO	DOMINICA
DR	DOMINICAN REPUBLIC
EB	EAST BERLIN
EC	ECUADOR
EG	EGYPT
ES	EL SALVADOR

EK	EQUATORIAL GUINEA
EN	ESTONIA
ET	ETHIOPIA
EU	EUROPA ISLAND
FA	FALKLAND/MALVINAS IS
FO	FAROE ISLANDS
FM	FEDSTS OF MICRONESIA
FJ	FIJI
FI	FINLAND
FR	FRANCE
FG	FRENCH GUIANA
FP	FRENCH POLYNESIA
FS	FR S&ANTARCTIC LANDS
GB	GABON
GA	GAMBIA, THE
GZ	GAZA STRIP
GC	GERMAN DEMOCRATIC R
GE	GERMANY FEDERAL R OF
GH	GHANA
GI	GIBRALTAR
GO	GLORIOSO ISLANDS
GR	GREECE
GL	GREENLAND
GJ	GRENADA
GP	GUADELOUPE
GQ	GUAM
GT	GUATEMALA
GK	GUERNSEY
GV	GUINEA
PU	GUINEA-BISSAU
GY	GUYANA
HA	HAITI
HM	HEARD IEMCDONALD IS
НО	HONDURAS
HK	HONG KONG
HQ	HOWLAND ISLAND
HU	HUNGARY
IC	ICELAND
IN	INDIA
ID	INDONESIA
IR	IRAN
IZ	IRAQ
IY	IRAQ-SAUDI ARABIA ZO
EI	IRELAND
IS	ISRAEL
IT	ITALY
IV	IVORY COAST
JM	JAMAICA
JN	JAN MAYEN
JA	JAPAN
DQ	JARVIS ISLAND
JE	JERSEY
JQ	JOHNSTON ATOLL
JO	JORDAN
JU	JUAN DE NOVA ISLAND

KE	KENYA
KO	KINGMAN REEF
KR	KIRIBATI
KN	KOREA DEMOCRATIC P R
KS	KOREA, R OF
KU	KUWAIT
LA	LAOS
LG	LATVIA
LE	LEBANON
LT	LESOTHO
LI	LIBERIA
LY	LIBYA
LH	LITHUANIA
LS	LIECHTENSTEIN
LU	LUXEMBOURG
MC	MACAU
MA	MADAGASCAR
MI MI	MALAWI
MY	MALAYSIA
MV	MALDIVES
ML	MALI
MT	MALTA
IM	MAN, ISLE OF
RM	MARSHALL ISLANDS
MB	MARTINIQUE
MR	MAURITANIA
MP	MAURITIUS
MF	
MX	MAYOTTE
	MEXICO
MQ MN	MIDWAY ISLANDS MONACO
	MONGOLIA
MG MH	MONTSERRAT
MO	MOROCCO
MZ	
WA	MOZAMBIQUE NAMIBIA
WA NB	
	NAURU NAVASSA ISLAND
BQ NP	NEPAL
NL	NETHERLANDS
NA NA	NETHERLANDS ANTILLES
NC NC	NEW CALEDONIA
NZ	NEW CALEDONIA
NU	NICARAGUA
= · · •	
NG	NIGER
NI	NIGERIA
NE	NIUE
NF	NORFOLK ISLAND
CQ	NORTHERN MARIANA IS
МО	NORWAY
OS	NO SOVEREIGNTY
MU	OMAN
PK	PAKISTAN
LQ	PALMYRA ATOLL
PM .	PANAMA

PP	PAPUA NEW GUINEA			
PF	PARACEL ISLANDS			
PA	PARAGUAY			
PE	PERU			
RP	PHILIPPINES			
PC	PITCAIRN ISLANDS			
PL	POLAND			
PO	PORTUGAL			
RQ	PUERTO RICO			
QA	QATAR			
QX	COLOMBIA/NICARAGUA			
QY	IRAN/UAE			
QZ	QATAR/BAHRAIN			
RE	REUNION			
RO	ROMANIA			
RW	RWANDA			
SC	ST CHRISTOPHER&NEVIS			
SH	SAINT HELENA			
ST	SAINT LUCIA			
SB	ST PIERRE & MIQUELON			
VC	ST VINC&GRENADINES			
SM	SAN MARINO			
TP	SAO TOME&PRINCIPE SAUDI ARABIA			
SA				
SG	SENEGAL			
SE	SEYCHELLES			
SL	SIERRA LEONE			
SN	SINGAPORE			
BP	SOLOMON ISLANDS			
SO SF	SOMALIA			
SP	SOUTH AFRICA			
PG	SPAIN			
CE	SPRATLY ISLANDS SRI LANKA			
SU	SUDAN			
NS				
SV	SURINAME SVALBARD			
WZ.	SWAZILAND			
SW	SWEDEN			
SZ				
SY	SWITZERLAND			
TZ	SYRIA			
TH	TANZANIA UNITED R OF THAILAND			
TO				
TL	TOGO			
TN	TOKELAU TONGA			
TD	TRINIDAD AND TOBAGO			
TE	TROMELIN ISLAND			
NQ	TR TE OF THE PACIFIC			
TS	TUNISIA			
TU	TURKEY			
TK	TURKS&CAICOS IS			
TV	TUVALU			
UG	UGANDA			
UR	U OF SOV SOC R			
V.1	0 01 001 000 K			

TC	UNITED ARAB EMIRATES
UK	UNITED KINGDOM
UN	UN CONTROL
US	UNITED STATES
UY	URUGUAY
NH	VANUATU
VT	VATICAN CITY
VE	VENEZUELA
VM	VIETNAM
VQ	VIRGIN ISLANDS
WQ	WAKE ISLAND
WE	WALLIS AND FUTUNA
WE	WEST BANK
WB	WEST BERLIN
WI	WESTERN SAHARA
WS	WESTERN SAMOA
YS	YEMEN (ADEN)
YE	YEMEN (SANAA)
YO	YUGOSLAVIA
CG	ZAIRE
ZA	ZAMBIA
ZI	ZIMBABWE
TW	TAIWAN
ZZ	CANARY ISLANDS

20. APPLICABLE DOCUMENTS This section is not applicable to this appendix.

APPENDIX D


WVS SEGMENT DIRECTION


10. GENERAL


10.1 <u>Scope</u>. To identify the features associated with segments in a WVS file, it is necessary to first identify the direction in which the segments are stored; e.g., the statement "Water is to the left of this segment" makes no sense unless the direction of "this segment" is given. WVS uses six different types of segment direction. These types are stored as one character codes (SEGDIR in the feature data records) and are identical to those used in DMA's Standard Linear Format (SLF). Each of these codes is described below, and examples are illustrated in Figure 6. This appendix is a mandatory part of thie specification. The information contained herein is intended for compliance.


SEGDIR	Direction	Description
F	Forward	Points are to be retrieved in the same order as stored (Figure 6a).
R	Reverse	Points are to be retrieved in the reverse of the stored order (Figure 6b).
D	Disjointed Forward	Same as Forward, but the segment is in a disjointed part of the area or linear feature (Figure 6c).
E	Disjointed Reverse	Same as Reverse, but the segment is in a disjointed part of the area or linear feature (Figure 6d).
I	Inside Forward	Same as Forward, but the segment describes a hole or island within an area feature (Figure 6e).
J	Inside Reverse	Same as Reverse, but the segment describes a hole or island within an area feature (Figure 6f).


20. APPLICABLE DOCUMENTS This section is not applicable to this appendix.














(e) Inside Forward (I), with Forward and Reverse:



(f) Inside Reverse (J), with Forward and Reverse:




FIGURE 6. Examples of segment direction.

INDEX

	PARAGRAPH	PAGE
Accuracy	. 3.1	2
Air standardization coordinating committee		
agreements (ASCC AIR STDs/STDs/ADV PUBs)	. 6.4.3	32
APPENDIX A Comparison of "chain-node" with		_
sequentially structured data		33
B Sample WVS file listing	•	35
C Country codes and country names		38
D WVS segment direction		44
Applicable documents		2
Cell description		7
Cell header		12
Country names		3
Data cells		11
Data records		9
Datum		3
Definitions		31
Executive orders		32
FACS features		16
Feature/Attribute requirements		16
Feature coordinates		9
Feature description		8
Feature records		12
File description.		4
File header records		10
File organization		7
File structure		10
Final product quality		31
General		3
ocherar	3.4.1	16
Government documents		2
Header records		9
Horizontal accuracy		3
Intended use		3 31
Inter-agency agreements		32
International MC&G agreements		32
International standardization agreements		31
International standardization agreements (STANAGS).		32
Non-Government publications		2
Notes	. b.	31
Order of precedence		2
Other documentation	. 6.4./	32
Other Government documents, drawings, and		_
publications	. 2.1.2	2
Packaging	. 5.	31
Physical characteristics of magnetic tape	. 3.3.2	4
Product classification	. 1.3.2	2
Product format		3
Purpose	. 1.2	1
Quadripartite standardization agreements (QSTAGs)		32
Requirements		2
Responsibility for compliance		31
Responsibility for inspection	4.1	31

<u>PARAGRAPH</u>	PAGE
Scope	1
Security	1
Security classification 1.3.1	1
Segment records	15
Specifications, standards, and handbooks 2.1.1	2
Supersession	31
Type of input/output	4
Vertical accuracy	3

CONCLUDING MATERIAL

Custodians: DMA - MP Preparing activity: DMA - MP

Review activities: Air Force - 09

(project MCGT-0015)

Army - CE Navy - NO

User activities: Air force - 09

Army - CDRUSAETL-CEETL-TC-SA; CDR25THINFDIV-APVG-DS; HQWESTCOM-APIN-MCG USAATCAAS-ASQ-AS-AI; USA-FSTC-CB1

Navy - HQFMFEUR-USNAVACTS-UK; CINCUSNAVEUR-N39, ECJ2-T; CINCUSPAC-J37

Marine Corps - CGFMFLANT-AC/S;
CGFMFPAC-AC/S; CGMCCDC-IN11

DMA - DMAAC-DAP; DMACSC-LANT; DMAHTC-IAGS, LOU-LUA, LOU-VRM, SXO-SXM

DMS - DMS-MTM

Other - Canada: HQND-MCE

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

- 1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
- 2. The submitter of this form must complete blocks 4, 5, 6, and 7.
- 3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT	DATE (YYMMDD)
THE COUNTY OF THE PROPERTY OF	MIL-W-89012	27 July	1990
3. DOCUMENT TITLE			
Military Specification for V 4. NATURE OF CHANGE (Identity paragraph of	World Vector Shoreline		
5. REASON FOR RECOMMENDATION			
LASUEMETER CARROLL CREMENT CONTROLLER		Maranda La Francia de C	i julia rejerenti segili e ilist
NAME (Last, First, Middle Sales)	b. ORGANIZA		
c. ADDRESS (Include 21p Code)	d TELEPHON (1) Commercia (2) AUTOVON (If applicat		7. DATE SUBMITTED. (YYAMGO).
. PREPARING ACTIVITY			
Defense Mapping Agency	(1) Commercia		(2) AUTOVON 356-9198
	(703)285		
ADDRESS (Include Zip Code)	IF YOU DO NO	OT RECEIVE A REPLY WITHIN	45 DAYS, CONTACT:

8613 Lee Highway, Fairfax, VA 22031-2137